

Technical Data

Jotun Thinner No. 4



Product description

Solvent thinner.

Recommended use

Thinner for zinc ethyl silicate paints.
Cleaner for equipment that has been used with waterborne products.

Consult the technical data sheet for the actual Jotun product.

Physical properties

Colour	Clear
Solids (vol %)*	0 ± 0
Flash point	12°C ± 2 (Setaflash)
VOC	6,5 lbs/gal (780 gms/ltr) USA-EPA Method 24 780 gms/ltr UK-PG6/23(97). Appendix 3

*Measured according to ISO 3233:1998 (E)

Storage

The product must be stored in accordance with national regulations. Preferred storage conditions are to keep the container in a dry space provided with adequate ventilation at room temperature (15-25°C). The containers should be sealed tightly.

Note: Low flash point.

Handling

Handle with care.

Packing size

5 litre container or 20 litre container.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at www.jotun.com

ISSUED 6 DECEMBER 2007 BY JOTUN
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED