



GVA 320000
FPSO

GVA 320 000 FPSO

Operation Area	Moderate environmental conditions
Hull configuration	Double side, Single bottom FPSO with Cargo tanks in pair
Classification	ABS
Accommodation	110 + 50 persons



Features:

- Purpose designed and fabrication friendly
- Cost efficient
- Service reliability
- Robust and fatigue reliable design
- Low motion characteristics
- Dead weight efficient

MAIN PARTICULARS		
Length over all	300 m	984.3 ft
Width over all	54 m	117.2 ft
Height	31.5 m	103.3 ft
Displacement	340,000 tonnes	374,785 s. tons
Topside	30,000 tonnes	33,070 s. tons
Length between perpendiculars	283.6 m	944.9 ft
Beam moulded	54.0 m	117.2 ft
Depth moulded	31.5 m	103.3 ft

TANK/STORAGE CAPACITIES		
Cargo oil/storage capacity	Min 265,530 m ³	Min 1 670,000 bbls
Slop capacity	6,780 m ³	42,645 bbls
Ballast capacity	113,300 m ³	712,636 bbls

Mailing address & Reg. office

GVA Consultants AB
P O Box 11450
SE-404 29 Gothenburg, Sweden

GVA North America
Sales Office, Houston

GVA Consultants AB
Sales Office, Brazil

Visiting address

Östra Hamngatan 7
41110 Gothenburg

1080 Eldridge Parkway
Houston, TX 77077
USA

Avenida Presidente Wilson 231, 5th floor
20030-021 Rio de Janeiro- RJ
Brazil

Telephone

Nat. 031 -10 67 00
Int. +46 3110 67 00

Phone. +1-281 529 2100
Fax. +1-281 529 2525

Phone: +55 21 2103 7608

E-mail

gva@gvac.se

Website

www.gvac.se