

6.1 GENERAL 总则

6.1.1 THREE FLANGE TYPE PIPE PART 6 PENETRATION PIECE SHALL BE GENERALLY USED.





三法兰式穿壁件

FOR THE SPACES WHERE THE SLEEVE WELDED JOINTS ARE USED WELDING SLEEVE TYPE PART 6 PENETRATION PIECES SHALL BE GENERALLY USED, BUT IN CASE THAT THE WELDING SLEEVE TYPE CAN NOT BE USED FOR ADJUSTMENT OF PIPE ALIGNMENT.

通常采用套管焊接式穿壁件，但是在有些需要管系改动的地方，套管穿壁件是不适用的

6.1.2 TYPE AND APPLICATION OF PART 6 PENETRATION PIECE TO BE GENERALLY IN ACCORDANCE WITH FOLLOWINGS.

穿壁件形式及应用如下所述：

| SKETCH 样式 | APPLICATION 应用 |
|--|---|
|  <p>THREE FLANGE TYPE 三法兰式</p> | TO BE APPLIED WHERE PIPES ARE CARRIED THROUGH WATERTIGHT BULKHEAD OR DECK, ETC. 用于水密壁及甲板 |
|  <p>SLEEVE TYPE 套管式</p> | TO BE APPLIED WHERE PIPES ARE CARRIED THROUGH WATERTIGHT BULKHEAD OR DECK, ETC. 用于水密壁及甲板 |
|  <p>OPEN TYPE 开口式</p> | TO BE APPLIED WHERE PIPES ARE CARRIED THROUGH NON-WATERTIGHT BULKHEAD OR DECK. 用于非水密壁及甲板 |
|  <p>NC-TYPE 贯穿式</p> | TO BE APPLIED WHERE PIPES ARE CARRIED THROUGH NON-TIGHT BULKHEAD GIRDER OR WEB WHICH DO NOT REQUIRE STRENGTH. 用于非水密梁材或附板，且不做强度要求 |