

SAONON SC SERIES-CUMMINS 50HZ

20-2000KW (25-2500KVA)

Genset Model	Standby/Prime Power		Engine Model	Cylinders	Displacement (L)	Fuel Consumption (L/H)	oil capacity (L)	coolant capacity (L)	Genset size(mm)			Weight (kg)
	KVA	KW							L	W	H	
SC25	25 / 22.5	20 / 18	4B3.9-G2	4L	3.9	4.3	11	17	1470	650	1146	650
SC30	30 / 27.5	24 / 22	4B3.9-G2	4L	3.9	5.2	11	17	1577	650	1146	670
SC40	40 / 37.5	32 / 30	4BT3.9-G2	4L	3.9	7	11	17	1685	650	1146	700
SC45	45 / 40	36 / 32	4BT3.9-G2	4L	3.9	8	11	18	1685	650	1146	710
SC55	55 / 50	44 / 40	4BTA3.9-G2	4L	3.9	10	11	18	1800	670	1190	830
SC62	62 / 56	50 / 45	4BTA3.9-G2	4L	3.9	12	11	18	1900	670	1190	850
SC70	70 / 63	56 / 50	4BTA3.9-G2	4L	3.9	14	11	18	2000	670	1190	870
SC80	80 / 72	65 / 59	6BT5.9-G2	6L	5.9	16	16	29	2100	790	1278	1000
SC90	90 / 85	72 / 68	6BT5.9-G2	6L	5.9	19	16	29	2200	790	1278	1063
SC110	110 / 100	88 / 80	6BT5.9-G2	6L	5.9	21	16	29	2200	790	1323	1098
SC125	125 / 114	100 / 91	6BTA5.9-G2	6L	5.9	31	16	29	2200	790	1323	1105
SC150	150 / 135	120 / 108	6BTAA5.9-G2	6L	5.9	33	16	30	2400	840	1323	1150
SC175	175 / 160	140 / 128	6CTA8.3-G2	6L	8.3	34	24	35	2480	860	1433	1450
SC200	200 / 180	160 / 144	6CTA8.3-G2	6L	8.3	38	24	39	2480	860	1433	1650
SC220	220 / 200	176 / 160	6CTAA8.3-G2	6L	8.3	43	24	47	2700	950	1460	1650
SC250	250 / 225	200 / 180	6LTAA8.9-G2	6L	8.9	47	24	47	2660	960	1454	1800
SC275	275 / 250	220 / 200	6LTAA8.9-G2	6L	8.9	55	37	62	2660	960	1454	1800
SC300	300 / 270	240 / 216	MTA11-G2A	6L	11	60	39	62	2950	1000	1571	2800
SC325	325 / 300	260 / 240	MTAA11-G3	6L	11	65	39	62	3100	1378	1644	2820
SC350	350 / 320	280 / 256	MTAA11-G3	6L	11	69	39	65	3100	1378	1644	2846
SC375	375 / 330	300 / 264	OSM11-G2	6L	11	70	38	62	3100	1378	1644	2846
SC388	388 / 350	310 / 280	NTA855-G2A	6L	14	73	39	65	3110	1000	1746	2880
SC400	400 / 363	320 / 290	NTA855-G4	6L	14	75	37	65	3110	1000	1746	2946
SC450	450 / 400	360 / 320	NTAA855-G7A	6L	14	89	37	65	3310	1378	1720	3100
SC500	500 / 450	400 / 360	KTA19-G3	6L	18.9	93	91	99	3615	1290	1912	3911
SC550	550 / 500	440 / 400	QSX15-G8	6L	15	103	91	99	3600	1300	1893	3911
SC575	575 / 520	460 / 416	KTA19-G4	6L	18.9	107	50	99	3615	1290	1912	4083
SC625	625 / 575	500 / 460	KTAA19-G5	6L	18.9	113	50	99	3860	1525	2059	4300
SC660	660 / 600	528 / 480	KTAA19-G6A	6L	18.9	119	50	195	3860	1525	2059	4449
SC688	688 / 625	550 / 500	KTAA19-G6A	6L	18.9	130	30	195	3860	1525	2059	4300
SC706	706 / 640	565 / 512	VTA28-G5	12V	28	140	83	265	3860	1590	1960	4449
SC825	825 / 750	660 / 600	VTA28-G6	12V	28	150	83	265	4400	1627	2444	7115
SC860	860 / 780	688 / 624	KTA38-G2	12V	37.8	167	83	265	4387	1808	2384	7794
SC900	900 / 815	720 / 652	OSK23-G3	12V	23	161	102	112	4169	1501	1918	6850
SC1000	1000 / 910	800 / 728	KTA38-G2A	12V	37.8	178	135	303	4387	1808	2384	7842
SC1050	1050 / 950	840 / 760	OST30-G3	12V	30	192	135	306	4400	1900	2444	8000
SC1100	1100 / 1000	880 / 800	OST30-G4	12V	30	204	135	309	4550	1900	2444	8017
SC1125	1125 / 1025	900 / 820	KTA38-G5	12V	37.8	185	135	309	4550	1900	2444	8600
SC1250	1250 / 1125	1000 / 900	KTA38-G9	12V	37.8	214	135	312	4550	1900	2444	8900
SC1375	1375 / 1250	1100 / 1000	KTAA38-G9A	12V	37.8	259	135	322	4755	2070	2444	9000
SC1400	1400 / 1275	1120 / 1020	KTA50-G3	16V	50.3	261	177	349	5319	1920	2520	9971
SC1675	1675 / 1500	1340 / 1200	KTA50-G8	16V	50.3	299	204	349	5319	2280	2542	10582
SC2063	2063 / 1875	1650 / 1500	OSK60G3	16V	60.2	320	280	378.5	6175	2286	2537	14649
SC2250	2250 / 2000	1800 / 1600	OSK60G4	16V	60.2	340	280	378.5	6175	2286	2537	14863
SC2500	2500 / 2250	2000 / 1800	OSK60G8	16V	60.2	360	280	378.5	6175	2286	2537	15200